


SUPER-X[®] PRO

High-precision stereo 2-way/mono 3-way crossover with subwoofer output



- ▲ Professional, high-precision stereo 2-way/mono 3-way crossover with separate subwoofer output
- ▲ World-class performance 24 dB per octave Linkwitz-Riley filters
- ▲ Absolutely flat summed amplitude response, zero phase difference
- ▲ Separate subwoofer section with independent frequency control
- ▲ Individual output level controls for all bands
- ▲ Individual output mutes for easy band adjustment
- ▲ Individual phase reverse switches for instant phase correction
- ▲ Switchable 25 Hz subsonic filter on each input for low-frequency driver protection
- ▲ Servo-balanced, gold-plated XLR connectors for all inputs and outputs
- ▲ Ultra-high precision ALPS potentiometers for ultimate accuracy and repeatability
- ▲ Ultra low-noise audio operational 4580 amplifiers for outstanding sound performance
- ▲ Illuminated switches for secure operation in dark stage environments
- ▲ High-quality components and exceptionally rugged construction for long life and reliability
- ▲ Shielded toroidal mains transformer for minimal noise interference
- ▲ Manufactured under ISO9000 certified management system

CX2310

SPECIFICATIONS

INPUTS

Connectors	XLR
Type	Electronically servo-balanced, HF filtered
Impedance	balanced >50 kOhm, unbalanced >25 kOhm
Max. Input level	+22 dBu typical, balanced or unbalanced
CMRR	>40 dB, typical >55 dB at 1 kHz

OUTPUTS

Connectors	XLR
Type	Electronically servo-balanced, HF filtered
Impedance	balanced 60 Ohm, unbalanced 30 Ohm
Max. Output level	+20 dBm balanced/unbalanced

PERFORMANCE

Bandwidth	20 Hz to 20 kHz, +0/-0.5 dB	
Frequency response	<5 Hz to >60 kHz, +0/-3 dB	
Signal to noise	Ref.: +4 dBu, 20 Hz to 20 kHz, unweighted	
	Stereo-Mode:	Mono-Mode:
Low output	>93 dB	>93 dB
Mid output		>95 dB
High output	>91 dB	>91 dB
Interchannel crosstalk	High to Low:	<93 dB
	High to Mid:	<94 dB
	Mid to Low:	<95 dB

CROSSOVER

Filter-Type	Linkwitz-Riley, 24 dB/octave, state-variable	
Mono Mode Frequencies	x1	x10
Low/High	44 to 930 Hz	440 Hz to 9.3 kHz
Low/Mid	44 to 930 Hz	440 Hz to 9.3 kHz
Mid/High	440 Hz to 9.3 kHz	
Stereo Mode Frequencies	x1	x10
Low/High	44 to 930 Hz	440 Hz to 9.3 kHz

POWER SUPPLY

Mains voltage	USA/Canada	120 V ~, 60 Hz
	U.K./Australia	240 V ~, 50 Hz
	Europe	230 V ~, 50 Hz
	General Export Model	100 - 120 V ~, 200 - 240 V ~, 50 - 60 Hz
Power consumption	<17 W	
Fuse	UL	100 -120 V ~: T 630 mA H
	Europe	200 - 240 V ~: T 315 mA H
	JP	90 - 110 V ~: T 630 mA H
Mains connection	Standard IEC receptacle	

PHYSICAL/WEIGHT

Dimensions	approx. 1 ¾" (44.5 mm) * 19" (482.6 mm) * 8 ½" (217 mm)
Weight	approx. 3 kg

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or illustrated.

The information contained in this manual is subject to change without notice. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of BEHRINGER Spezielle Studiotechnik GmbH.

BEHRINGER and SUPER-X are registered trademarks. ALL RIGHTS RESERVED.

© 2001 BEHRINGER Spezielle Studiotechnik GmbH.

BEHRINGER Spezielle Studiotechnik GmbH, Hanns-Martin-Schleyer-Str. 36-38, 47877 Willich-Münchheide II, Germany

Tel. +49 (0) 21 54 / 92 06-0, Fax +49 (0) 21 54 / 92 06-30
