

**EUROLIVE P1020/P1220/P1220F/P1520/P2520/P1800S**

# Technical Specifications

en

Version 1.0 December 2006



[www.behringer.com](http://www.behringer.com)



# EUROLIVE

## EUROLIVE P-SERIES

en

- ▲ Professional PA Speaker system
- ▲ Exceptional sound quality, wide frequency bandwidth and dynamic range
- ▲ Extremely powerful long-excursion drivers provide incredibly deep bass and acoustic power
- ▲ State-of-the-art 1.75" titanium-diaphragm compression driver for exceptional high-frequency reproduction (except P1800S)
- ▲ State-of-the-art horn design for ultra-wide sound dispersion (except P1800S)
- ▲ Overload-protection circuitry ensures optimal HF driver protection
- ▲ Ergonomically shaped handles for easy transport
- ▲ Rugged steel grill for optimal speaker protection
- ▲ 2 professional speaker connectors plus 1/4" jack connectors
- ▲ High-quality components and exceptionally rugged construction ensure long life
- ▲ Conceived and designed by BEHRINGER Germany

SERIES

## SPECIFICATIONS

	P1020	P1220	P1220F	P1520	P2520	P1800S
<b>SYSTEM DATA</b>						
Continuous Power (IEC268-5)	75 W	80 W	80 W	160 W	225 W	425 W
Peak Power	300 W	320 W		640 W	900 W	1700 W
Type	2-way full-range speaker					subwoofer
Frequency response	70 Hz – 20 kHz	60 Hz – 20 kHz		50 Hz – 20 kHz	45 Hz – 20 kHz	35 Hz – 250 Hz
Impedance	8 Ohm				4 Ohm	
Sound pressure level	98 dB (Full Space; 1 W @ 1 m)					98 dB (1W @ 1m)
Dispersion	90° x 40°					-
Crossover frequency	3.5 kHz				2.7 kHz	- (200 Hz recommended)
Rigging/fittings	- ergonomically shaped handles - integral tripod/stand adaptor	ergonomically shaped handle	- ergonomically shaped handles - integral tripod/stand adaptor	ergonomically shaped handles	- ergonomically shaped handles - 35-mm pole socket	
<b>COMPONENTS</b>						
HF driver	1.75" titanium-diaphragm compression driver					-
Woofers	10" (259 mm)	12" (307 mm)		15" (385 mm)	2 x 15" (385 mm)	18" (460 mm)
<b>DIMENSIONS/WEIGHT</b>						
Width	14.8 / 8.8" (375 / 223 mm)	16.5 / 10.6" (420 / 270 mm)	16.7" (424 mm)	18.1 / 12" (459 / 305 mm)	21.5" (545 mm)	26.5" (672 mm)
Height	20.3" (515 mm)	21.4" (544 mm)	21.7" (550 mm)	25.4" (645 mm)	43.6" (1108 mm)	33.5" (850 mm)
Depth	13" (330 mm)	13.1" (332 mm)	13" / 4.5" (330 / 115 mm)	13.1" (332 mm)	19.6" (497 mm)	17.6" (446 mm)
Weight	30.9 lbs (14 kg)	37.7 lbs (17.1 kg)	35.9 lbs (16.3 kg)	46.3 lbs (21 kg)	90.4 lbs (41 kg)	108.5 lbs (49.2 kg)
Shipping weight	35.3 lbs (16 kg)	41.9 lbs (19 kg)	39.7 lbs (18 kg)	48.5 lbs (22 kg)	94.8 lbs (43 kg)	116.8 lbs (53 kg)

en

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or illustrated.

Technical specifications and appearance subject to change without notice. The information contained herein is correct at the time of printing. All trademarks (except BEHRINGER, the BEHRINGER logo, JUST LISTEN, EUROLIVE and EUROPOWER) mentioned belong to their respective owners, and such use neither constitutes a claim of the trademarks by BEHRINGER nor affiliation of the trademark owners with BEHRINGER. BEHRINGER accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph or statement contained herein. Colors and specifications may vary slightly from product. Products are sold through our authorized dealers only. Distributors and dealers are not agents of BEHRINGER and have absolutely no authority to bind BEHRINGER by any express or implied undertaking or representation. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of BEHRINGER International GmbH.

ALL RIGHTS RESERVED. © 2006 BEHRINGER International GmbH,  
Hanns-Martin-Schleyer-Str. 36-38, 47877 Willich-Münchheide II, Germany.  
Tel. +49 2154 9206 0, Fax +49 2154 9206 4903