

## POWERED SPEAKER



### FEATURES

- **POWERED SPEAKER**  
Rated output power is 20W/4Ω.
- **SOUND AND STRUCTURE**  
Designed for compact sound system with very strong structure - form enclosure.
- **2 WAY SPEAKER SYSTEM**  
To assure absolute long-term reliability, those model are used by woofer and tweeter of high quality.
- **2 MIC INPUT AND AUX INPUT**  
Mic 1, 2 input are designed with electrical balance circuit to protect hum and induction in case of long cable of signals. And for the convenient use of system, AUX input is provided.
- **2 BAND TONE CONTROL**  
Equalizer of 2 band has controlled a gain range of ±12dB. Center frequency is 200Hz and 8KHz.

### SPECIFICATIONS

#### ■ ELECTRICAL

##### AMP SECTION

- Rated Output(4Ω, THD 10%) .....20W
- Input Sensitivity/Impedance  
Mic1, 2.....-50dB/600Ω, BAL  
AUX .....-10dB/10KΩ, UNBAL
- Frequency Response(+1/-3dB)  
Mic Input.....250Hz~12KHz  
AUX.....80Hz~18KHz
- Tone Control  
Treble(8KHz).....±12dB  
Bass(200Hz) .....±12dB
- Residual Noise(all VR max) .....45dB

##### SPEAKER SECTION

	WOOFER	TWEETER
Frequency Response	80Hz~5KHz	1.1KHz~20KHz
Input Level(nomi/max)	15W/30W	15W/30W
Impedance/SPL	4Ω/90dB	4Ω/90dB

#### ■ GENERAL

- Power Source .....AC 110V~240V, 50/60Hz, DC 12V
- Power Consumption.....120V:18W  
230V:23W  
240V:19W
- Weight.....4.6Kg
- Dimensions .....345(W) X 205(H) X 173(D)mm