



DPA-1036/1048/1060

DIGITAL POWER AMPLIFIER



Features

- Digital Public Address Power Amplifier 360W / 480W / 600W.
- Advanced switch-mode power supply technology for high performance (SMPS).
- Compact Size – All models only 1 HU for reduced rack cost and space.
- 2 XLR Input connectors with link capability.
- Full protected circuitry design : shot circuit, thermal overload and turn on delay.
- High Pass Filter.
- Light Weight – All models only 5.5 Kg for easier racking and shipping.
- High efficiency design (Class D), Light Weight.

Specification

Rated Output	DPA-1036 360W RMS, 70V/15Ω, 100V/30 Ω DPA-1048 480W RMS, 70V/10Ω, 100V/20 Ω DPA-1060 600W RMS, 70V/8Ω, 100V/16 Ω
Frequency Response (-3Db)	80Hz~18KHz
T.H.D (at 1 KHz Rated Output)	Less Than 0.4%
Signal To Noise Ratio Output)	Better Than 90dB
Input Sensitivity	1.0V
High Pass Filter	450Hz
Power Efficiency	Better Than 85%~90%
Dimension	482 (W) x 44(H) x 400(d) mm
Weight	5.5 Kg
Power Source	AC 120V~240V, 50/60 Hz , 24DC