

# HOUSING & BRACKET



## INDOOR HOUSING



PIH-5040S

### PIH-5040S

- Mounting : Bottom
- Construction : Aluminum
- Window Dimension (mm) : 74 (W) x 64 (H)
- Dimension (mm) : 140 (W) x 115 (H) x 373 (D)
- Weight(Kg) : 1.3



PIH-5020

### PIH-5020

- Mounting : Bottom
- Construction : Aluminum
- Window Dimension (mm) : 84 (W) x 60 (H)
- Dimension (mm) : 124 (W) x 95 (H) x 395 (D)
- Weight(Kg) : 1.22

## OUTDOOR HOUSING



PIH-5030

### PIH-5030

- Mounting : Bottom
- Construction : Aluminum
- Window Dimension (mm) : 84 (W) x 60 (H)
- Dimension (mm) : 142 (W) x 104 (H) x 386 (D)
- Weight(Kg) : 2.50
- Ext. Model : PIH-5030H (Heater)  
PIH-5030B (Blower)  
PIH-5030HB (Heater & Blower)



PIH-5040

### PIH-5040

- Mounting : Bottom
- Construction : Aluminum
- Window Dimension (mm) : 84 (W) x 60 (H)
- Dimension (mm) : 142 (W) x 104 (H) x 386 (D)
- Weight(Kg) : 2.0

## OUTDOOR PRESSURIZED HOUSING



PIH-5050

### PIH-5050

- Mounting: Bottom
- Construction: Stainless AISI S316
- Window: 6mm Tempered Glass
- Rating: IP 68
- Air Filling: Dry Nitrogen
- Seal Connector: Seal Metal 14 Pins Connector
- Safety Pressure Valve: Adjustable 5 ~ 15 PSI
- Air Pressure Test: Max. 20 PSI
- Sunshield: Option
- Heater Activation: +15°C ~ +25°C
- Power Input: AC 220V / AC 110V / AC 24V
- Dimension (mm): 470(L) x 170(W) x 193(H) x 134(Inner Dia)
- Weight: 10.5Kg

# BRACKET



PIH-500 PIH-500L PIH-5001N PIH-5005M

## PIH-500 / 500L / 5001N / 5005M CAMERA BRACKET

Adjustment : Pan - 360° Tilt - ±90°  
 Maximum Load : 2 Kg / 5 Kg (5005M)  
 Construction : ABS Injection (PIH-500, 500L)  
 : Aluminum (PIH-5001N, 5005M)  
 Dimension(mm) : 500 - 76 (W) x 153 (H) x 73 (D)  
 : 500L - 76 (W) x 218 (H) x 73 (D)  
 : 5001N - 123 (L) x 45 (ø)  
 : 5005M - 164 (L) x 119 (ø)  
 Weight : 500 - 80g  
 : 500L - 100g  
 : 5001N - 110g  
 : 5005M - 280g



PIH-5003

PIH-5004

## PIH-5003 SCANNER BRACKET PIH-5004 CAMERA BRACKET

Adjustment : Pan & Tilt(PIH-5004)  
 Maximum Load : 10 Kg  
 Construction : Aluminum, Light Gray Textured  
 Dimension(mm) : 85 (W) x 309 (H) x 99 (D)  
 Weight(Kg) : 0.45(PIH-5003) ; 0.6(PIH-5004)



PIH-303BX

## PIH-303BX INDOOR BRACKET FOR FASTDOME

Maximum Load : 30 Kg  
 Construction : Steel, Light Gray Textured  
 Dimension(mm) : 318.5 (W) x 214 (H) x 180 (D)  
 Weight(Kg) : 3.9



PIH-301B

PIH-303B

PIH-303P

## PIH-301B / PIH-303B / PIH-303P OUTDOOR BRACKET

Maximum Load : 30 Kg  
 Construction : 301B-Steel, Silver Gray Baked Enamel Finish  
 : 303B 303P-Aluminum, Light Gray Textured  
 Dimension : 301B-248 (W) x 470 (H) x 200 (D)  
 : 303B-148 (W) x 385 (H) x 175 (D)  
 : 303P-148 (W) x 335 (H) x 175 (D)  
 Weight : 301B-3.6Kg ; 303B-1.2Kg ; 303P-1.1Kg  
 Extension Tube : PIH-303PEX (30cm)



PIH-301BH

## PIH-301BH PILOT HEAD

Adjustment : Pan & Tilt  
 Maximum Load : 15 Kg  
 Construction : Aluminum, Silver Gray Baked Enamel Finish  
 Dimension(mm) : 177 (W) x 109 (H) x 106 (D)  
 Weight(Kg) : 0.8



PIH-CM / PIH-PM

## PIH-CM / PIH-PM OUTDOOR CORNER / POLE MOUNT

Maximum Load : Corner Mount-50 Kg Pole Mount-25 Kg  
 Construction : Aluminum, Light Gray Textured, 8mm Thick  
 Strap : Pole Mount- 2 Stainless Strap for Pole  
 : Diameter Range 2.5 ~ 7 Inch  
 Weight(Kg) : Corner Mount-2.5 ; Pole Mount-2

# OUTDOOR DOME HOUSING

The PIH-510 series is IP68 rated camera outdoor dome housing. Designed to house a single Li Lin's fast dome (PTZ) camera or a single fixed camera. This decorative housing features a flame resistant ABS top dome and a vandal resistant polycarbonate lower cover. Providing camera complete protection from vandalism. It is available in three models; wall mounting (PIH-510L), Pendant mounting (PIH-510H) and Swan Neck (PIH-510G). All models come with built-in heater and fan.



PIH-510L  
PIH-510LIP



PIH-510H  
PIH-510HIP

## PIH-510 Outdoor Dome Housing

Model No.	PIH-510G PIH-510GIP	PIH-510H PIH-510HIP	PIH-510L PIH-510LIP
Type	Swan Neck	Pendant Mount	Wall Mount
Heater Activation	On:<15°C Off:>25°C		
Fan Activation	On:>35°C Off:<25°C		
Input Voltage	DC 12V		
Dimension (mm)	Total Height	875	477.5
	Total Width	685	274
	Dome (ø)	270	270
	Base(ø)	180	
Weight(Kg)	10	4.8	5



PIH-510G  
PIH-510GIP

## FEATURES

- Sealed to protect internal camera from moisture and dust
- Meet CE/IP68 standard
- Built-in heater and fan to maintain camera in normal operation temperature
- Heavy-duty construction provides complete protection from vandalism
- Bracket: Aluminum, Silver Gray
- Top Dome: Flame Resistant ABS
- Internal Fixing: Steel
- Lower Dome: Polycarbonate (clear or tinted)
- Extension Tube: PIH-Z6 (30cm)

**Li Lin**  
MERIT LI-LIN ENT. CO., LTD.  
[www.meritlilin.com](http://www.meritlilin.com)

