9LILIN.





dynamic range video compression rate 40:1~240:1(automatically adjusted according to the video condition). Compared with the other compression format, H.264 has the longer recording period so it will save the cost of storage and avoid the burden of replacing the HDD frequently. Useful functions include live real-time audio, multiple alarm triggers such as motion detection & motion tracer, 3~5 pre alarm recording...ect. PVH-AH264 is fashion in the shape, small in the cubage, easy to use and convenient to install. It is the perfect solution for varies application especially for the locations with

limited spaces.

Recording Speed 240MAX~200MIN fps (NTSC)

200MAX~167MIN fps (PAL)

S.M.A.R.T. Smart Monitoring, Analysis, and Reporting Technology. System will auto detect. analysis and reporting the status of HDD.

## Multi-task Capability

Supports Recording, Playback, Remote Monitoring and Live Monitoring at the same time.



- Technology: H.264 Hardware real time compression / decompression
- Resolution: 704 x 480 (NTSC) / 704 X 576 (PAL)
- Image Compression Rate: Dynamic Compression Rate = 40:1~240:1 (Automatic Changes depends on the image's moving situation).
- Average Dynamic Compression Rate: 40:1~2400:1
- Recording Quality: 10 Levels Adjustment available
- Maudio Recording: 24Kbps ADPCM recording mode. Synchronize with Video Recording.
- Live Audio Monitoring: Support Live Audio Monitoring.
- Internet Function: Support TCP/IP functions. Support internet / LAN remote monitoring.
- Playback (search) mode: Playback directly by selected time, search by saved time log, and by alarm log. Up to 4CH playback.
- File Backup Function: Support USB disk for backup or retrieve files from appropriative remote software.
- Playback backup files: Playback using Lilin Player (V5.4 or above) directly from a computer.
- Firmware Update: Firmware update available.

0	model and	Total Control of the	- The rest of
DATAL	ALC: N	Ballan It B	
SDE	82 H H I	157.6	
$\sim$			200

Models	PVH-AH264	
System	Standalong, Linux	
Built-in DVD/CD		
Removable HDD tray	None	
Internal HDD support	2	
HDD supported	IDE	
Ecternal RAID support	None	
Recording	H.264	
2000	PAL:200~167 fps	
Speed	NTSC:240~200 fps	
Deschalies	PAL:704 x 576	
Resolution	NTSC:704 x 480	
Schedule	Time, daily,weekly	
Audio Backup	Yes	
Video Input		
Looping	None	
Channel Editing	None	
Video Out	1 BNC (1Vp-p, 75W)	
VGA output	1024 x 768	
Split screen	1, 4, 8, 16	
Spot	None	
Alarm		
Motion	Area x 4	
Pre-recording	3~5 secs / Yes	
Accessories		
P/T/Z protocol		
Keyboards	None	
Jog & shuttle	None	
Mouse support	Yes	
Audio	RCA x 16 inputs	
Network	RCA x 1 output	
Remote firmware upgrade	None	
Web	Yes	
Two-way audio	None	
Mobile/PDA support	None	
DST	None	
Multilanguage	English, Chinese	
Power	AC 115V 4A	
	230V 2A	
Dimension	340 mm (W)	
	205 mm (D)	
	190 mm (H)	





