933BW • 2233SW • 2233BW • 2433BW

SAMSUNG

19", 21.5", 22" and 24" Widescreen LCD Monitors



Features:

- Distinctive soft design with rich piano black finish
- Integrated rear cable housing for a clean look
- Up to 1920 x 1080 full HD resolution (2233SW)
- 5ms response, up to 20,000:1 dynamic contrast ratio
- Exclusive Samsung Magic technologies for rich, natural color
- Custom key for one-touch access to preferred picture function
- 16:10 aspect ratio, 16:9 aspect ratio widescreen (2233SW)







933BW

2233SW/BW 2433BW

imagine a sculpture that doubles as a valuable business tool. That's the Samsung 33BW/SW series widescreen LCD monitors. Their soft curves, rich piano black finishes, clear acrylic accent bars and integrated cable housings lend distinctive style and sophistication to your desk. The widescreens mean more room for multitasking, while up to 1920 x 1080 full HD resolution, 5ms response, exclusive picture technologies and up to 20,000:1 dynamic contrast ratio give you fast, colorful, detailed motion video. Beauty inside and out. With the Samsung 33BW/SW series, it's not hard to imagine.

933BW 2233SW 2233BW 2433BW



19," 21.5," 22" and 24" Widescreen LCD Monitors

Features	Specifications		933BW	2233SW	2233BW	2433BW
	Display	Туре	a-si TFT/TN	a-si TFT/TN	a-si TFT/TN	a-si TFT/TN
Distinctive Design		Viewable Size	19" Wide	21.5" Wide	22" Wide	24" Wide
Soft corners, rich piano black finish and		Native Resolution	1440 x 900	1920 x 1080	1680 x 1050	1920 x 1200
acrylic accent bar will beautify any desk.		Pixel Pitch (mm)	0.285	0.248	0.282	0.270
Cable Ususing		Aspect Ratio	16:10	16:9	16:10	16:10
Cable Housing		Contrast Ratio	1000:1/15000:1 Dynamic	1000:1/15000:1 Dynamic	1000:1/20000:1 Dynamic	1000:1/20000:1 Dynamic
Integrated rear housing hides cables,		Viewing Angle (H/V)	170°/160° (CR>10)	160°/160° (CR>10)	170°/160° (CR>10)	170°/160° (CR>10)
for a sleek, clean look.		Response Time	5ms	5ms	5ms	5ms
Up to 1920 x 1080 Full HD The 2233SW features 1920 x 1080 full HD resolution, giving you the highest resolution possible.		Light Source	CCFL	CCFL	CCFL	CCFL
		Brightness (Typical)	300 cd/m ²	300 cd/m ²	300 cd/m ²	300 cd/m ²
		Panel Surface	Matte	Matte	Matte	Matte
	Video Input Signal	Maximum Color Supported	16.7M	16.7M	16.7M	16.7M
		Analog	Analog RGB	Analog RGB	Analog RGB	Analog RGB
Custom Key		Digital	DVI (with HDCP)	DVI (with HDCP)	DVI (with HDCP)	DVI (with HDCP)
The programmable Custom Key gives		Frequency (H/V)	30~81kHz(H) / 56~75Hz(V)	30~81kHz(H) / 56~75Hz(V)	30~81kHz(H) / 56~75Hz(V)	30~81kHz(H) / 56~75Hz(V)
you instant one-touch access to your		Sync	H/V Separated, Composite	H/V Separated, Composite	H/V Separated, Composite	H/V Separated, Composite
preferred Samsung picture optimization technology. MagicBright 3 gives you	L		H/V, Sync on Green	H/V, Sync on Green	H/V, Sync on Green	H/V, Sync on Green
	Compatibilty	PC	Windows Vista Premium Certification, XP, 2000, 98	Windows Vista Premium Certification, XP, 2000, 98	Windows Vista Premium Certification, XP, 2000, 98	Windows Vista Premium Certification, XP, 2000, 98
seven pre-set modes to choose from.		Mac	Mac OS Leopard, X, 9	Mac OS Leopard, X, 9	Mac OS Leopard, X, 9	Mac OS Leopard, X, 9
MagicColor enhances color either overall or with regard to natural skin	Input Connectors		15-pin D-sub, DVI-D, 3-pin AC plug (CEE22)	15-pin D-sub, DVI-D, 3-pin AC plug (CEE22)	15-pin D-sub, DVI-D, 3-pin AC plug (CEE22)	15-pin D-sub, DVI-D, 3-pin AC plug (CEE22)
tones. Color Effect lets you view images in grayscale, green, aqua or sepia. And Image Size lets you properly view either 5:4 or 4:3 content on the widescreen without distortion.	Power	Voltage	AC 100-240 ~ VAC (±10%), 60/50 Hz ± 3 Hz	AC 100-240 ~ VAC (±10%), 60/50 Hz ± 3 Hz	AC 100-240 ~ VAC (±10%), 60/50 Hz ± 3 Hz	AC 100-240 ~ VAC (±10%), 60/50 Hz ± 3 Hz
		Consumption (Max/DPMS)	34 watts /<1 watt	40 watts/<1 watt	45 watts/<1 watt	50 watts/<1 watt
	Controls	Basic	Power, Auto Adjustment, Source, Brightness up/down, MagicBright 3 presets, OSD Menu	Power, Auto Adjustment, Source, Brightness up/down, MagicBright 3 presets, OSD Menu	Power, Auto Adjustment, Source, Brightness up/down, MagicBright 3 presets, OSD Menu	Power, Auto Adjustment, Source, Brightness up/down, MagicBright 3 presets, OSD Menu
2433BW Dimensions			Picture (Brightness, Contrast, Magic Bright), Color (MagicColor, Tone, Control, Effect, Gamma), Image (Coarse, Fine, Sharpness, H position, V position, V position, Transparency, Display Time), Setup (Auto Source, Reset, Off Timer, Customized Key, Image Size)	Picture (Brightness, Contrast, Magic Bright), Color (MagicColor, Tone, Control, Effect, Gamma), Image (Coarse, Fine, Sharpness, H position, Twe, Sharpness, H position, Twensparency, Display Time), Setup (Auto Source, Reset, Off Timer, Customized Key, Image Size)	Picture (Brightness, Contrast, Magic Bright), Color (MagicColor, Tone, Control, Effect, Gamma), Image (Coarse, Fine, Sharpness, H position, Twe, Sharpness, H position, Twensparency, Display Time), Setup (Auto Source, Reset, Off Timer, Customized Key, Image Size)	Picture (Brightness, Contrast, Magic Bright), Color (MagicColor, Tone, Control, (MagicColor, Tone, Control, Coarase, Fine, Sharpness, H position, Y position, V position, Transparency, Display Tinne), Setup (Auto Source, Reset, Off Timer, Customized Key, Image Size)
	Features	Plug & Play	DDC 2B/DDC-CI	DDC 2B/DDC-CI	DDC 2B/DDC-CI	DDC 2B/DDC-CI
		Stand	Tilt	Tilt	Tilt	Tilt
		Wall Mount (VESA)	75mm	100 mm	100mm	100mm
		Cabinet Color	High Gloss Black	High Gloss Black	High Gloss Black	High Gloss Black
	Magic Technologies	MagicColor (Full/ Intelligent) MagicBright 3 (Custom, Text, Internet, Game, Sport, Movie, Dynamic Contrast)	•	•	•	•
		MagicTune (On-screen Asset Management)			•	•
17.9"	Operating Conditions	Temperature	10°~ 40°	10°~ 40°	10°~ 40°	10°~ 40°
		Humidity	10% ~ 80%, non-condensing	10% ~ 80%, non-condensing	10% ~ 80%, non-condensing	10% ~ 80%, non-condensir
	Dimensions and Weight	W x H x D With Stand, W x H x D Without Stand Shipping Carton	17.8" x 14.9" x 7.9" 17.8" x 13.1" x 2.9 20.4" x 15.9" x 5.2"	20.4" x 15.4" x 8.2" 20.4" x 13.6" x 2.8" 23.5" x 16.3" x 5.2"	20.3" x 16.6" x 8.2" 20.3" x 14.7" x 2.8" 23.5" x 17.3" x 5.2"	22.4" x 17.9" x 8.6" 22.4" x 15.9" x 2.8" 25.9" x 19.6" x 5.4"
		Weight (w/Stand, Shipping)	8.8 lbs., 11.9 lbs.	9.7 lbs., 12.9 lbs.	10.6 lbs., 13.7 lbs.	11.7 lbs., 15.0 lbs.
	Package Contents		Monitor, Power Cable, 15-pin D-sub Cable, DVI-D Cable, Manuals, Driver CD	Monitor, Power Cable, 15-pin D-sub Cable, DVI-D Cable, Manuals, Driver CD	Monitor, Power Cable, 15-pin D-sub Cable, DVI-D Cable, Manuals, Driver CD	Monitor, Power Cable, 15-pin D-sub Cable, DVI-D Cable, Manuals, Driver CD
	Warranty		3 years parts and labor	3 years parts and labor	3 years parts and labor	3 years parts and labor
	Green Management	Emission Standard	EMC	EMC	EMC	EMC
		RoHS Compliant				
		Energy Star Compliant				
8.6"		Product Recyclability	CCFL panel contains mercury, please dispose of properly	CCFL panel contains mercury, please dispose of properly	CCFL panel contains mercury, please dispose of properly	CCFL panel contains mercury please dispose of properly
		Packaging Recyclability	Packing materials recyclable	Packing materials recyclable	Packing materials recyclable	Packing materials recyclable

Product Information: 1-866-542-7214 Product Support: 1-800-SAMSUNG

www.samsungmonitors.com



©2008 Samsung Electronics America, Inc. Samsung is a registered mark of Samsung Electronics Corp., Ltd. Specifications and design are subject to change without notice. See www.samsung.com for detailed information. Printed in USA. MON-33SeriesDSHT-Sep08T