

PDG-DSU20N

SVGA Ultraportable Multimedia Projector



ULTRA-COMPACT, FULLY PORTABLE SVGA DESIGN

Not much larger than a laptop PC, the PDG-DSU20 weighs less than 6.5 pounds and delivers true SVGA picture quality in a versatile, go-anywhere system.

HIGH BRIGHTNESS AND CONTRAST

A brightness level of 2000 ANSI Lumens and a contrast ratio of 2000:1 make this projector a winner in its category.

F2.51-2.69 ZOOM LENS

Comes with its own 1:1.1 zoom lens, which can throw a crisp, bright 100" diagonal image.

AUTO INPUT SEARCH

Searches, finds and displays incoming source material automatically.

SPECIAL FEATURES

Component input, quiet fan operation and versatile go anywhere capability make this a truly portable projector. Also may be ceiling or inverse mounted for enhanced versatility.

SOFT CARRYING CASE

Zip and go case great for carrying and storing the projector.

SANYO

PRESENTATION TECHNOLOGIES

21605 Plummer Street
 Chatsworth, CA 91311
 Ph: 888-337-1215 (toll-free)
 Fax 818.717.2719
 www.sanyolcd.com

Specifications

Resolution	SVGA (800 x 600)
Brightness	2000 ANSI Lumens
Uniformity	80% (corner to center)
LCD Panel System	0.55" DMD x 1
Number of Pixels	480,000(800 x 600)
Contrast Ratio	2000:1
Image Size (diagonal)	27.8" - 255"
Aspect Ratio	4:3
Throw Distance	3.9' - 39.4'
Zoom/Focus	Manual
Zoom Ratio	1:1.1
Up/Down Ratio	13.3:1
Digital Keystone Correction	Vertical: +/- 15° MAX
Projection Lens	F2.51-2.69 / f0.86"-0.95"
Lens Throw Ratio	1.95-2.15:1
Projection Lamp	180W UHP
Scanning Frequency	H Sync: 31-79kHz, V Sync: 50-85Hz
Dot Clock	25-135MHz
Color System	PAL/PAL-M/PAL-N/SECAM/NTSC/NTSC4.43
Computer Compatibility	SXGA, XGA, SVGA, VGA
Sound Output	One-piece, 2-watt Mono
Voltage	100-240V AC (auto Voltage) ; 50/60 Hz
BTU Rating	853
dB Rating	35dB / 32dB (Normal/Eco)
Power Consumption	230W / 200W (Normal/Eco)
Dimensions (WxHxD)	10.7" x 3.7" x 8.8" (not including Adjustable Feet & Lens Part)
Net Weight	5.5lbs
User Maintenance	replace lamp assembly
PC Input Terminals	D-Sub15 x 1
Video Input Terminals	Composite Video (RCA x 1) • S-Video (Mini-DIN 4-pin) • Audio(stereo mini-jack : common)
Control Terminals	• USB (Type B)
Included Accessories	Wireless remote • CR2025 batteries • Owner's Manual • VGA Cable • Lens Cap with strap • Soft Carrying Bag • AC power supply code
Optional Accessories	• POA-CA-COMPVGA - Component- VGA conversion Cable • 610 337 1764 - Replacement Lamp
Service Port	n/a
Warranty	Three years parts and labor; 90 days original lamp; Quick Repair Program under warranty

Because its products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.



INPUT / OUTPUT TERMINAL



REMOTE CONTROL



DLP® and the DLP logo are registered trademarks of Texas Instruments.