

# PLV-Z2000 TopazReal HD

## 16:9 Full HD, High Contrast Home Entertainment Projector



### FULL HIGH-DEFINITION RESOLUTION – 1080p

Offering a full 1920 x 1080 high-definition resolution, the PLV-Z2000 delivers rich, deep and accurate colors due to SANYO's exclusive Topaz Real HD Technology, a 3D color management system that addresses changes in color phase and color level to obtain perfect color reproduction. The PLV-Z2000's color management system provides 1110 times more color combinations than SANYO's 720p PLV-Z5, a total of approximately 216 billion possible color combinations. This new color management system was designed to optimize the potential of deep color via the projector's two HDMI 1.3 inputs.

### LENS MAXIMIZATION OF IMAGE DETAIL

Rated at 1200 lumens, the PLV-Z2000 is capable of an incredible 15,000:1 contrast ratio for superlative black levels, even in ambient light. Plus it has a newly-developed, high-efficiency lens that maximizes image details for exceptional optical performance.

### NEW OPTICAL SYSTEM FOR RELIABILITY AND PERFORMANCE

The PLV-Z2000 uses a Durable Inorganic Optical System (D.I.O.S.). This highly advanced optical engine increases the overall reliability and performance of the PLV-Z2000 many times over traditional 3LCD projectors.

### ADVANCED LENS SHIFT FOR VARIOUS ROOM ENVIRONMENTS

The PLV-Z2000 is outfitted with the industry's most advanced lens shifting function. When coupled with the projector's short throw capability and 2x zoom, the PLV-Z2000 can create a large screen image in any size room and from virtually any location. The lens shifting function allows wide-range shifting up or down to three screen sizes and left to right to two screen sizes. The throw design of the PLV-Z2000, which is capable of projecting a 100-inch diagonal image from 10 to 20 feet away, makes it extremely suitable for small to mid-size home theaters.

### VIRTUALLY SILENT FAN DESIGN

A 1200 lumen projector generates a tremendous amount of heat and requires a high quality fan to ensure proper operation. At this level of brightness, the fan is 'on' most of the time and the noise can be extremely loud and disruptive, especially in smaller home theaters where the projector and the audience are in the same vicinity. To promote greater enjoyment of the film and to reduce noise levels during quiet passages of a film, the PLV-Z2000 is equipped with the industry's quietest fan, a large aperture, low noise Sirocco cooling fan that never rises above 19dB in the economy mode.

**SANYO**

PRESENTATION TECHNOLOGIES

21605 Plummer Street  
Chatsworth, CA 91311  
Ph: 888-337-1215 (toll-free)  
Fax 818.717.2719  
www.sanyolcd.com

## Specifications

Resolution	1920 x 1080
Brightness (typical)	1,200 ANSI Lumens (vivid mode)
Uniformity	85% (corner to center)
LCD Panel System	0.74" TFT Poly-Silicon x 3 (16:9)
Number of Pixels	6,220,800(2,073,600 x 3)
Contrast Ratio	15000:1 (vivid mode)
Projection Image (diag.)	40" ~ 300"
Aspect Ratio	16:9
Throw Distance	3.9' ~ 60.4'
Zoom/Focus	1x to 2.0x, Manual driven
Lens Shift	Manual (Up/ Down/Left/Right)
Up/Down/Left/Right Ratio	Up/Down: 3: -1 ~ -1:3 (-1V/Center/+1V) Left/Right: 10:0 ~ 0:10 (-0.5H/Center/+0.5H)
Digital Keystone Correction	No
Projection System	Dichroic mirror & 4P prism system w/ PBS
Projection Lens	F2.0 ~ 3.0 / f0.9" ~ 1.8"
Lens Throw Ratio	1.35 ~ 2.7:1
Projection Lamp	165W UHP
Scanning Frequency	H: 15-80kHz, V: 50-100Hz (auto sense/select)
Dot Clock	100MHz
Color System	PAL/SECAM/NTSC/NTSC4.43/PAL-M/PAL-N
Computer Compatibility	WXGA/SXGA/XGA/SVGA/VGA/MAC
Voltage	100V-240V AC: 50/60Hz (auto voltage)
BTU Rating	860
dB Rating	19dBA (Eco mode)
Power Consumption	252W
Dimensions (WxHxD)	15.7" x 5.7" x 13.6" (not including Adjustable Feet)
Net Weight	16.1 lbs.
User Maintenance	Clean air filters, replace lamp assembly
Input Terminals	
Component Video 1	Y, Pb/Cb, Pr/Cr (RCA x 3)
Component Video 2	Y, Pb/Cb, Pr/Cr (RCA x 3)
S-Video	S-Video (Mini DIN 4-pin x 1)
Composite Video	Video (RCA x 1)
Computer	Analog RGB (D-Sub 15)
HDMI 19-Pin DVI	HDMI (19-pin) x 2
Communication	RS-232C/ Service Port (Mini DIN 8-pin)
Included Accessories	Owner's Manual(Quick manual & CD ROM); Illuminated Infrared Remote Control; AC Power Cord (6.6'); 2 AA batteries Air blower
Optional Accessories	6103365404 – Replacement Lamp
FCC Rating	Class B, UL Listed
Warranty	3-years parts & labor; 90-days lamp (original); 30-days lamp (replacement) Quick Repair Program under warranty

Because its products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.



Illuminated Remote Control



Rear Panel Terminals



Motorized Front Door